




## Tubular COB Line Series



### Key Features & Benefits

The new COB LED source provides unified color and light output and is ideal to replace **G9 base pendant or cabin** and crystal lighting fixtures. Available: 2W, 3W and 5W options. This bulb is highly versatile and offers significant energy savings and environmentally friendly. Light output is 360° which is perfect for even dispersion applications.

### Technical Specifications:

Model Name	JQ-G9-C02K30 [3000K]	JQ-G9-C03K27 [2700K] JQ-G9-C03K30 [3000K]	JQ-G9-C05K27 [2700K] JQ-G9-C05K30 [3000K] JQ-G9-C05K40 [4000K]
Photo			
Halogen Replacement	<b>25W</b>	<b>30W</b>	<b>50 Watt</b>
Shape & Base	G9	G9	G9
Operating Voltage:	120VAC	120VAC	120VAC
Power consumption:	2W	3W	5 Watt
Dimmable: *	Yes	Yes	Yes
Dimensions:	0.62"x0.38"x1.10"(tall)	0.62"x0.38"x1.10"(tall)	0.62"x1.65"(tall)
CRI:	86	86	86
CCT Option:	2700K/3000K	2700K/3000K	2700K/3000K/4000K
Luminous Flux:	200lm	300lm	400lm.
Operating Temperature:	-20° C - +50° C	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C	-30° C - +60° C
IP Rating:	IP67	IP67	IP67
Safety Certification:	<b>ETL, FCC Compliance</b>	<b>ETL, FCC Compliance</b>	<b>ETL, FCC Compliance</b>
Rated Lifespan:	>25,000hrs.	>25,000hrs.	>25,000hrs.

**Notes:** Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5% ; Dimmable\* fully tested with LUTRON© DVCL, DVCL etc.