

GBF



Bayonet DC Base



Key Features & Benefits

The MR11 bayonet double contact base series LED light integrates a set of COB LED light sources into a traditional **MR11 bayonet double contact base** track or cabin lighting. There are two options: 2W IP54 and 3W IP68 rating which is the ideal solution for outdoor damp environment. It meets basic lighting requirements, offers significant energy savings, and is environmentally friendly.

Technical Specifications:

Model Name	JQ-GBF-A03K27M [CCT: 2700K] JQ-GBF-A03K30M [CCT: 3000K]	JQ-GBF-B03K27M [CCT: 2700K] JQ-GBF-B03K30M [CCT: 3000K]
Product Photo		
Halogen Replacement	25 Watt	20 Watt
Operating Voltage:	9 ~ 15VAC/DC	9 ~ 15VAC/DC
Power consumption:	2.5 Watt	2 Watt
Dimming:	Yes	Yes
Dimensions:	1.97"x1.38"D	1.80"x1.38"D
CRI:	>80	>80
CCT Option:	2700K,3000K	2700K,3000K
Luminous Flux:	230 lm	160 lm
Operating Temperature:	-20° C - +50° C	-20° C - +50° C
Storage Temperature:	-30° C - +60° C	-30° C - +60° C
View Angle	36°	36°
IP Rating	IP68	IP54
Safety Certification:	FCC Compliance	FCC Compliance
Rated Lifespan:	>25,000hrs.	>25,000hrs.

Notes: Wattage +/- 10%; Lumen Values +/- 5Lms. CRI +/- 5%; **Dimmable*** fully tested with LUTRON© magnetic dimmer or electrical dimmer with minimum load.

JQ Green America Inc.

San Diego Office: (714)837-7155 Fax: (888)653-8693
Miami Office: (786)397-0999
Houston Office: (772)301-2967

© Copyright 2024 JQ Green America Inc.